


RFID HARD TAG HT066

MARKETS:



Industry



Logistics

The HT066 is a highly specialised RFID hard tag crafted from ferrite, a ceramic-like material boasting excellent magnetic properties and electrical insulation. Rectangular in shape, the HT066 is incredibly **small and lightweight, measuring just 4 x 2 x 2 mm and weighing a mere 0.3 grams. It's specifically designed to be embedded within metallic objects, thereby enhancing their NFC technology capabilities.** This tag is also engineered to withstand challenging environments, tolerating heat up to 200°C and cold down to -60°C!

The HT066 is available in **HF (High Frequency) with an ICODE SLIX chip and integrated NFC technology.**

MARKETS

Thanks to its extremely small size, the HT066 can be incorporated into metallic objects for inventory organisation, as well as for **product traceability and identification**, providing a discreet yet robust solution for various industrial needs.



frequency 13,56 MHz

RFID features

Chip	Memory	ISO Standard	NFC Standard
ICODE SLIX	128 bytes - UID: 8 bytes	ISO 15693	Type 5 - tag compliant

Technical specifications

Application	Metal surfaces
Dimensions	4 x 2 x 2 mm
Material	Ferrite
Weight	0.3 g
Application method	Embedding
Operating temperature	-40°C ~ +85°C
Storage temperature	-60°C ~ +200°C

