

RFID HARD TAG HT067

MARKETS:



Industry



Logistics



COLORS:



Yellow

The HT067 is a robust RFID hard tag made from high-performance engineered plastic, offering superior resistance to mechanical impacts, chemical reagents, and both low and high temperatures. Rectangular in shape, the HT067 weighs approximately 19 grams and measures 54 x 36 x 12.5 mm. It's specifically designed for application on dense metallic surfaces, where it can be securely attached with adhesive backing or via screws. Available in yellow, this tag operates on both **European and US UHF frequencies and is equipped with the UCODE 8 chip.**

The HT067 can be customised using laser technology.

MARKETS

With an IP68 rating, the HT067 is completely impermeable to water and dust. This makes it an ideal solution for **asset management projects, inventory control, and industrial automation**, particularly in environments with dense metal assets that demand high durability and reliable performance.



European frequency (EU) 868 MHz - US frequency 920 MHz

RFID features

Chip	Memory	ISO Standard
UCODE 8	0 bytes - TID: 12 bytes - EPC: 16 bytes	EPC Class 1 Gen 2
UCODE 8 US	0 bytes - TID: 12 bytes - EPC: 16 bytes	EPC Class 1 Gen 2

Technical specifications

Application	Metal surfaces
IP rating	68
Dimensions	54 x 36 x 12.5 mm
Material	Engineering plastic
Weight	19.5 g
Application method	Adhesive or screws
Operating and storage temperature	-40°C ~ +85°C

Customisation

Colour	Yellow
Type of printing and numbering	Laser technology

