




### COLOURS:



Black

Blue

Pink

Yellow

The WB002 is a RFID wristband for **women**, exclusively Made in Italy. Crafted from durable polyurethane, it offers excellent resistance to water, salt water, and humidity. Featuring an **open cuff**, the dial of this wristband is white and can be customised using offset and epoxy printing, while serial numbering can be applied using laser or inkjet technology. The WB002 is available in **Low Frequency (LF)**, it supports **EM4200, ATA5577 or T5567, EM4550 or TITAN, HITAG2, HITAG S 2048, and HITAG S 256.** For **High Frequency (HF)**, it is compatible with **MIFARE CLASSIC 1K EV1 S50, MIFARE CLASSIC 4K EV1 S70, MIFARE ULTRALIGHT EV1-1, MIFARE ULTRALIGHT EV1-2, MIFARE ULTRALIGHT C, TAG-IT 256, TAG-IT 2K.**

## RFID WRISTBAND WB002

### MARKETS:



Campsites



Hotels



Gyms



Vending

The WB002 is available in a selection of colours: **black, blue, pink, and yellow.**

### MARKETS

With its unique, modern design, WB002 is waterproof and easy to wear. It is ideal for **access control and identification at swimming pools, hot springs, water and leisure parks, campsites and tourist resorts.** In addition, they can act as electronic wallets to purchase snacks and soft drinks at vending machines, make payments at cafés or restaurants, and activate additional personal services.



frequency 125 kHz

#### RFID features

Chip	Memory	ISO Standard
EM4200	0 bytes - UID: 8 bytes	ISO 11784 / 11785
EM4550 or TITAN	128 bytes - UID: 8 bytes	ISO 11784 / 11785
ATA5577 or T5567	36 bytes - UID: 8 bytes	ISO 11784 / 11785
HITAG2	32 bytes	ISO 11784 / 11785
HITAG S 2048	256 bytes - UID: 4 bytes	ISO 11784 / 11785
HITAG S 256	32 bytes - UID: 4 bytes	ISO 11784 / 11785



frequency 13.56 MHz

#### features RFID

Chip	Memory	ISO Standard	NFC Standard
MIFARE CLASSIC 1K EV1 S50	1024 bytes - UID: 4 bytes	ISO 14443 A	Not supported by majority of NFC devices
MIFARE CLASSIC 1K EV1 S50 7 BYTES	1024 bytes - UID: 7 bytes	ISO 14443 A	Not supported by majority of NFC devices
MIFARE CLASSIC 4K EV1 S70	4096 bytes - UID: 4 bytes	ISO 14443 A	Type 2 - tag compliant
MIFARE ULTRALIGHT EV1-1	48 bytes - UID: 7 bytes	ISO 14443 A	Type 2 - tag compliant
MIFARE ULTRALIGHT EV1-2	128 bytes - UID: 7 bytes	ISO 14443 A	Type 2 - tag compliant
MIFARE ULTRALIGHT C	144 bytes - UID: 7 bytes	ISO 14443 A	Type 2 - tag compliant
TAG-IT 256	32 bytes - UID: 8 bytes	ISO 15693	Type 5 - tag compliant
TAG-IT 2K	256 bytes - UID: 8 bytes	ISO 15693	Type 5 - tag compliant



#### Technical specifications

<b>Wristband dimensions</b>	ø 200 x 15 mm (Size: M)
<b>Dial dimensions</b>	ø 55 mm (printable area)
<b>Gender</b>	Female
<b>Material</b>	Polyurethane
<b>Operating temperature</b>	-20°C ~ +55°C
<b>Storage temperature</b>	-20°C ~ +85°C

#### Customisation

<b>Type of printing on dial</b>	Offset, epoxy printing
<b>Type of numbering</b>	Laser, inkjet technology
<b>Strap colours</b>	Black, blue, pink, yellow
<b>Dial colours</b>	White

